
DATA SHEET

TRAC AC 10W S **Updated 2018/5/14**

Downlight





COMPLIANCE
IEC60598 IEC62778
IEC62471

PHYSICAL CHARACTERISTICS

INSTALLATION	Surface mounted
CUT-OUT SIZE	n/a
DIMENSION	Ø52mm x H80mm
LENGTH	n/a
CEILING THICKNESS RANGE	n/a
FIXING SYSTEM	Screw
ADJUSTABILITY	n/a
ROTATION	n/a
IP-RATING	IP20
IK-RATING	IK03
FIXTURE MATERIAL	Housing: Die-Cast Aluminum
STANDARD FINISH	White / Black
FINISH TYPE	Powder Coating

ELECTRIC / PHOTOMETRIC DATA

LIGHT SOURCE	C291023
CHROMATICITY TOLERANCE	SDCM-3
LED CURRENT	n/a
NOMINAL POWER	9.9 W
NOM LUMINOUS FLUX	955 lm
NOMINAL EFFICACY	96 lm/W
SYSTEM POWER	9.9 W
LUMINAIRE LUMINOUS FLUX	525 lm
SYSTEM EFFICACY	53 lm/W
COLOR RENDITION OPTIONS	Ra ⩾ 90, R9 ⩾ 50
COLOR TEMPERATURE	2700K
BEAM ANGLE OPTIONS	15° / 25°/ 40°
DIMMING OPTION(S)	TRIAC

MISCELLANEOUS SPECIFICATIONS


ENERGY CLASS	A
MAINS VOLTAGE	100-240 V AC
FREQUENCY	50/60 Hz
SAFETY CLASS	III
ENVIRONMENTAL TEMP.	-20°C / +40°C
RATED SERVICE LIFE (h)	n/a
WARRANTY	3 years

DATA SHEET


TRAC AC 10W S **Updated 2018/5/14**

Downlight


PHOTOMETRICS



15D



25D



40D

OPTIONAL ACCESSORIES

HONEYCOMB LOUVER 

FROSTED LENS

CLEAR LENS 