

TITAN40W(Downlight 天花燈)

INSTALLATION INSTRUCTION 安裝說明










Step.1 步驟.一


Rotate the front ring counterclockwise and remove it.

把前環以逆時針方式旋轉除去。




Fasten the top cover on the ceiling with screw.

將頂蓋用螺絲鞏固在天花板。




Rotate the reflector counterclockwise and remove it.

把反光杯以逆時針方式旋轉除去。




Connect the live wire and neutral wire of the cable to the corresponding PRI slot in the driver.

將火線和中線與驅動器的PRI插口連接。




Remove the screw and separate the top cover and the body part.

拆去螺絲並將頂蓋和主體部件分離。




Connect the positive wire and negative wire of the 1-10V signal wire to the corresponding positive and negative slot in the driver.

將正極線和負極線與驅動器的正負插口連接。



Pass the cable wire through the big hole and 1-10V signal wire through the small hole in the top cover.

把電線穿過頂蓋的大開孔和把1-10V訊號線穿 過頂蓋的大開孔。



Pass the screw through the big hole of the body part and fasten it to the top cover.

將螺絲穿過主體部件的大開孔並與頂蓋鎖好。



TITAN40W(Downlight 天花燈)

INSTALLATION INSTRUCTION 安裝說明










Step.9

步驟.九



Make sure the screw head is about 1mm above the middle plate in the body part.


注意螺絲頭和主體部件的間板相隔大慨1mm距離。



Rotate the front ring clockwise and lock it.


把前環以順時針方式旋轉鎖緊。





Rotate the body part counterclockwise to lock it with the top cover together.

把主體部件以逆時針方式旋轉與頂蓋鎖緊。




Installation is finished.

安裝完成。




步驟.十一




Pass the female connector through the hole in the body part and connect it with the male connector of the led.


將母插穿過主體部件的開孔與LED的公插連接



Rotate the reflector clockwise and lock it.

把反光杯以順時針方式旋轉鎖緊。







Luminaires not suitable for covering with thermally insulating material.

任何情況下,燈具都不能被隔熱襯墊或 類似的材料覆蓋。



 The luminaire shall be installed by a qualified electrician and wired in accordance with the lastest IEE electrical regulations or the national requirements.

本產品必須交由專業人士安裝,且電線必須符合最新電氣標準或國家漂準法規。

2. Please ensure the minimum of 40mm gqp from the top.

必須確保本產品的頂部至少有40mm的間隙。

3. There is risk of electric shock.

有觸電的危險。


4. Please cut off the power before installation and maintenance.

在安裝或維護前,請先切斷電源。

5. Pease consult qualified engineer if any question about the installation instruction. 若有任何疑問,請向持有資格證書的工程師諮詢。

- Do not touch the reflecting surface inside the reflector by hand. 請勿用手觸摸反光罩內表面。
- 7. This lamp is not suitable for the work after the installation of ceiling brush powder, brush powder is likely to damage the surface of the lamp and lead to the srface of the skin off. 此燈具並不適合安裝後再做天花刷粉工作,刷粉有可能破壞燈具表面處理而導致表皮脫落。
- 8. All with corrosive cleaning supplies or chemical substances must not be exposed to the lamp so as to avoid damage.

所有帶腐蝕性清潔用品或化學物質紹不能接觸燈具以免造成損壞。



INSTALLATION INSTRUCTION

安裝說明









