
DATA SHEET

TADDEO I TRIMLESS **Updated 2018/5/14**

Downlight





COMPLIANCE
IEC60598 IEC62778
IEC62471

PHYSICAL CHARACTERISTICS

INSTALLATION	Recessed
CUT-OUT SIZE	Ø91mm
DIMENSION	Ø89.5mm x H118mm
LENGTH	155mm
CEILING THICKNESS RANGE	n/a
FIXING SYSTEM	Recessed
ADJUSTABILITY	n/a
ROTATION	n/a
IP-RATING	IP20/IP44
IK-RATING	IK03
FIXTURE MATERIAL	Housing: Die-Cast Aluminum
STANDARD FINISH	White / Black
FINISH TYPE	Powder Coating

ELECTRIC / PHOTOMETRIC DATA

LIGHT SOURCE	CLU028-1204C4
CHROMATICITY TOLERANCE	SDCM-3
LED CURRENT	400 mA
NOMINAL POWER	13.7 W
NOM LUMINOUS FLUX	1663 lm
NOMINAL EFFICACY	121 lm/W
SYSTEM POWER	15.2 W
LUMINAIRE LUMINOUS FLUX	915 lm
SYSTEM EFFICACY	60 lm/W
COLOR RENDITION OPTIONS	Ra ⩾ 90, R9 ⩾ 50
COLOR TEMPERATURE	4000K
BEAM ANGLE OPTIONS	15° / 25° / 40°/ 60°
DIMMING OPTION(S)	TRIAC, 1-10V, DALI

MISCELLANEOUS SPECIFICATIONS

ENERGY CLASS	A
MAINS VOLTAGE	100-240 V AC
FREQUENCY	50/60 Hz
SAFETY CLASS	III
ENVIRONMENTAL TEMP.	-20°C / +40°C
RATED SERVICE LIFE (h)	50,000
WARRANTY	5 years

DATA SHEET


TADDEO I TRIMLESS **Updated 2018/5/14**

Downlight


RECOMMENDED DRIVER OPTIONS / SPECIFICATIONS

DRIVER (MFR#)	DIMMING OPTIONS	DIMENSIONS (L x W x H)	OUTPUT POWER	OUTPUT CURRENT	POWER FACTOR	EFFICIENCY	RIPPLE CURRENT
TCI #122201	On / Off	110.4 x 52 x 22mm	20W	400mA	0,97	>88	≤ 3%
TCI #123400	1-10V & PUSH	103 x 67 x 30mm	18W	350mA	0,95	>89	≤ 3%
TCI #123403	DALI	110.4 x 52 x 22mm	17W	400mA	0,92	>87	≤ 3%
TCI #127030	TRIAC	110.4 x 52 x 22mm	18W	350mA	0,95	>89	≤ 20%


PHOTOMETRICS




15D



25D



40D



60D

OPTIONAL ACCESSORIES

HONEYCOMB LOUVER 

FROSTED LENS

CLEAR LENS 